

## LED Floodlights



### VT-4850

#### HIGHLIGHTS :

WATTS



50

EQ. WATTS



250

LUMINOUS



4000

BEAM ANGLE



100

|                            |                     |
|----------------------------|---------------------|
| Item No                    | : VT-4850           |
| SKU Code                   | : 5682              |
| Watts                      | : 50                |
| EQ. Watts                  | : 250               |
| Voltage                    | : 100-240V,50/60Hz  |
| Lumen(lm)                  | : 4000              |
| Color Temperature          | : 3000K             |
| Beam Angle                 | : 100               |
| PF                         | : >0.95             |
| LED Chip Type              | : SMD               |
| CRI                        | : >70               |
| Energy rating label        | : A+                |
| Certification              | : CE,EMC,ROHS       |
| IP Rating Protection Class | : IP65              |
| Body type                  | : DIE CAST ALUMINUM |
| Dimmable                   | : No                |
| Life Time                  | : >20000 Hours      |
| Operation Temperature      | : -25 ~50°C         |
| EAN code                   | : 3800157603416     |
| Unit size                  | : 296x225x40mm      |
| Packing details            | : 10.00             |
| Unit cbm                   | : 0.00250           |

#### PRODUCT FEATURES

- Available in White , Warm White and RGB Light output option
- Premium Quality Aluminium Alloy body
- Corrosion Resistant
- Built in Power supply, No external ballast required
- PIR Sensor Movement Detector – Optional
- Widely used for Lighting Driveways, Gardens & Buildings, Commercial Bill, Boards & Hoardings, Plazas, Sports Grounds & Parking Lots

