

Product Specification Sheet



100W

VT-49101 100W SMD SLIM FLOODLIGHT COLORCODE:3000K WHITE BODY,WHITE WIRE

Lumens 8500 Beam Angle 100

Dimensions 291x240x30mm

Warm White SKU:5970










Technical Information

Instant Start:	0-100% in lt1s
Watts:	100
Lumens:	8500
Beam Angle:	100
Unit Color:	White
Body Type:	Aluminium Die Cast
Energy Rating:	A+
Long life:	20,000 Hours

LED Chip Type:	SMD
IP Rating:	IP65
Dimmable:	No
Warranty (Years):	2
PF:	>0.9
CRI:	>70
Input Power:	AC:220-240V,50Hz
Sensor Compatibility:	Yes



Features

✓ Perfect replacement of Metal Hallide Floodlight, High Pressure Sodium Floodlight & Halogen Floodlight

Available in different color options of White, Day White, Warm White and RGB

Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance

Premium Quality Aluminium Alloy body

High Power LED chip

Corrosion Resistant

Built in driver - no external power supply required

Excellent coverage for area and façade lighting

Available from 10W up to 1000W

Application - Building Façade, Sports Facilities, Industrial, Commercial Bill Boards & Hoardings, Parking Lots etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details

Gross Weight(GW) Kgs	1.75
Length(Box)mm	250
Width(Box)mm	300
Height(Box)mm	40
Unit CBM	0.003452
Master Box Packaging	

Master Box Qty (Pcs Per Carton)	4
Qty Per Pallet	280

Listing Details

EAN Code	3800157626231
Commodity Code	9405403990

